









MAGNET DRILL FOR PIPES ECO TUBE 55-T

| Cutters | Twistdrills | Countersink | Threading |
|---|---|---|---|
|  |  |  |  |
| 55 mm | 1600 W | 860 kg | 170 mm |
| 23/16" | 15/16" | 23/8" | 13/16" |

| Weight | Motor | Magnet | |
|---|---|---|---|
|  |  |  |  |
| 17,6 kg | 1600 W | 860 kg | 170 mm |
| 39 lbs | 14.5 A | 1895 lbs | 6.6" |

| CW/CCW rotation | Soft start | Overload protection | Heat protection |
|---|---|---|---|
|  |  |  |  |

| Oil bath gearbox | Digital display | LED load indicators | Smart restart | Gyro-Tec |
|---|---|---|---|---|
|  |  |  |  |  |

- No electricity required for magnetic base
- For flat and round (as from \varnothing 80mm / 3 1/2") surface.
- No special attachments needed
- Highly stable wide stance
- Two separate magnets which allows the machine to swing away for hole inspection debris removal without losing position
- Integrated oil bath gearbox
- External access to auto shut-off carbon brushes
- Digital power read-out display & Smart Restart technology



GYRO-TEC

GYRO TEC is powered by a state of the art gyroscopic sensor, triggering automatic motor shut-off when detecting displacement in any direction. It detects:

- Sudden loss of adhesion
- Excessive vibration
- Sudden displacement of the workpiece

Technical details:

| | |
|------------------|--|
| Annular cutters: | \varnothing 55 mm |
| Twist drills: | \varnothing 23 mm |
| Countersink: | \varnothing 60 mm |
| Threading: | M20 |
| Length: | 320 mm |
| Width: | 210 mm |
| Height: | 523 - 693 mm |
| Stroke: | 170 mm |
| Weight: | 17,6 kg |
| Magnet (LxBxH): | 266x239x82 mm |
| Magnetic force: | 860 kg |
| Motor power: | 1600 W |
| Speed (no load): | 185-530 U/min |
| Speed (load): | 250-460 U/min |
| Spindle: | MT3 19,5 mm Weldon |
| Voltage: | 110 - 120 V / 50-60 Hz 220 - 240 V / 50-60 Hz |

